

CABLES



Type	Finish	Index	Copper purity [%]
Stranded	Black insulation	006-005	99,97
Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	1 x 0,35	22	6



Type	Finish	Index	Copper purity [%]
Stranded	Black insulation	006-0015	99,97
Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	1 x 0,50	20	7

CABLES



Type	Finish	Index	Copper purity [%]
Stranded	Red Insulation	006-0020	99,97
Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	1 x 0,50	20	7



Type	Finish	Index	Copper purity [%]
Stranded	Black insulation	006-0025	99.97
Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	1 x 0,75	18	11

CABLES



Type	Finish	Index	Copper purity [%]
Stranded	Blue Insulation	006-0030	99,97
Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	1 x 0,75	18	11



Type	Finish	Index	Copper purity [%]
Stranded	Orange Insulation	006-0035	99,97
Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	1 x 0,75	18	11

CABLES



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Stranded	Red Insultation	006-0040	99,97
----------	-----------------	----------	-------

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	1 x 0,75	18	11
----	----------	----	----



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Stranded	Black PTFE	006-0045	99,9
----------	------------	----------	------

***Silver plated**

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

600	1 x 1,3	16	15
-----	---------	----	----

CABLES



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Stranded	Red PTFE	006-0050	99,9
----------	----------	----------	------

* Silver plated

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

600	1 x 1,3	16	15
-----	---------	----	----



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Stranded	Black PTFE	006-0051	99,9
----------	------------	----------	------

* Silver plated

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

600	1 x 2,5	13	33
-----	---------	----	----

CABLES



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Stranded	Red PTFE	006-0052	99,9
----------	----------	----------	------

* Silver plated

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

600	1 x 2,5	13	33
-----	---------	----	----



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Solid Core	Blue PE	006-0070	99,99
------------	---------	----------	-------

*Full range OFC 4N

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 0,50	20	42
----	----------	----	----

CABLES



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Solid Core	Blue PE	006-0080	99,99
------------	---------	----------	-------

***Full range OFC 4N**

Max. Volt	Cross sec. [mm ²]	AWG	Weight: g/ Meter
-----------	-------------------------------	-----	------------------

80	2 x 1,00	17	55
----	----------	----	----



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Solid Core	Blue PE	006-0085	99,99
------------	---------	----------	-------

***Full range OFC 4N**

Max. Volt	Cross sec. [mm ²]	AWG	Weight: g/ Meter
-----------	-------------------------------	-----	------------------

80	2 x 1,0 + 2 x 0,5	17/20	63
----	-------------------	-------	----

CABLES



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Stranded	Transparent insulat.	006-0090	99,99
----------	----------------------	----------	-------

*OFC 715 4N

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 1,5	15	42
----	---------	----	----



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Flat Braided	Transparent insulat.	006-0095	99,99
--------------	----------------------	----------	-------

*OFC 4N

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 1,5	15	42
----	---------	----	----

CABLES



Type	Finish	Index	Copper purity [%]
Stranded	Black/Red PVC	006-0100	99,99
*OFC 4N			
Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	2 x 1,5	15	42



Type	Finish	Index	Copper purity [%]
Stranded	Black/Red PVC	006-0105	99,99
*USA Line	*OFC 4N		
Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	2 x 1,5	15	63

CABLES



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Stranded	Transparent insulat.	006-0110	99,99
----------	----------------------	-----------------	-------

***OFC 4N**

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 2,5	13	62
----	---------	----	----



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Flat Braided	Transparent insulat.	006-0115	99,99
--------------	----------------------	-----------------	-------

***OFC 4N**

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 2,5	13	73
----	---------	----	----

CABLES



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Stranded	Black PVC	006-0120	99,99
----------	-----------	-----------------	-------

***OFC 4N**

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 2,5	13	68
----	---------	----	----



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Stranded	White PVC	006-0125	99,99
----------	-----------	-----------------	-------

***OFC 4N**

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 2,5	13	68
----	---------	----	----

CABLES



Type	Finish	Index	Copper purity [%]
Twill Weave	Trans. Insu. / Black	006-0130	99,97
Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	2 x 2,5	13	72



Type	Finish	Index	Copper purity [%]
Twill Weave	Trans. Insu. / Blue	006-0135	99,97
Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	2 x 2,5	13	72

CABLES



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Twill Weave	Trans. Insu. / Green	006-0140	99,97
-------------	----------------------	-----------------	-------

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 2,5	13	72
----	---------	----	----



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Twill Weave	Trans. Insu. / White	006-0145	99,97
-------------	----------------------	-----------------	-------

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 2,5	13	72
----	---------	----	----

CABLES



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Twill Weave	Trans. Insu. / Yellow	006-0150	99,97
-------------	-----------------------	-----------------	-------

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 2,5	13	72
----	---------	----	----



Type	Finish	Index	Copper purity [%]
------	--------	-------	-------------------

Stranded	Transparent Insulat.	006-0155	99,99
----------	----------------------	-----------------	-------

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
-----------	------------------	-----	------------------

80	2 x 4,0	11	110
----	---------	----	-----

CABLES



Type	Finish	Index	Copper purity [%]
Standard	Black PVC	006-0208	99,9

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	2 x 0,75	18	16



Type	Finish	Index	Copper purity [%]
Standard	White / Blue PVS	006-0215	99,9

Max. Volt	Cross sec. [mm2]	AWG	Weight: g/ Meter
80	2 x 1,0	17	24